



# MarineCork

## Tips for installation and for maintenance



The MarineCork Cork is flexible but must not be rolled or stretched, it must always be handled flat to avoid the formation of cracks due to excessive bending.

The material can be cut with jigsaw cutters or circular saws.

- **Make sure that the surface to be coated is homogeneous** and there are no irregularities.
- **Clean and degrease the top** before gluing.
- **Position the slats / panels** according to the drawing to follow.
- **Tape the perimeter of the surface to be bonded** with blue adhesive tape (which does not release glue).
- **Apply the adhesive evenly over the entire surface** with a notched trowel with 3 mm teeth (external temperature  $>10^{\circ}$   $<35^{\circ}$ ).
- When you have placed the cork on the glue, **use a roller by pressing to make it adhere well** and so that any air bubbles are eliminated.
- **Block the planks / panels** glued together with adhesive tape.

Periodic washing and cleaning of MarineCork panels is recommended.



See how to:

Install



Rubber and caulking



Protect



Repair





## Tips for installation and for maintenance

- **If possible, place wooden boards with weights on top** to ensure perfect bonding.
- Once the gluing is finished, **the joints can be filled with rubber of the chosen color.**
- Before putting the rubber for the comments, **pass the primer with a brush inside the channel and let it dry for 30 min.**
- **Use a 600ml cartridge gun.**
- **After filling the joints, let the product dry for 2-3 days,** it depends on the humidity.
- **Sand the entire surface with an orbital sander** until the filling of the joints is perfectly smooth with 120 grit paper, always round the outer edges with sandpaper.
- **Finally wash with water and a brush to remove all the dust** generated by sanding (do not use high pressure pumps).
- **When the surface is dry, apply the Cork Protect. \***



\* Before using Cork Protect shake the package vigorously for at least 5 minutes, pour the product into a container suitable for immersion of the brush or roller. When pouring back into the bowl, always shake the package first for 2 minutes.

The product must always be shaken and worked immediately to keep the particles always in suspension.

Seasonally it is recommended to carry out maintenance of the installed surface with MarineCork by applying the protective CorkProtect. Obviously the affected surface must be, as needed, cleaned, washed and sanded before applying CorkProtect.

For more information

✉ [info@marinecork.com](mailto:info@marinecork.com)

☎ +39 348.8363587

marinecork